



Thermodyn™
Where Your Success Is Sealed

Black Utility Grade Rubber

Product Code: Style 6106
Description: 60 Durometer Rubber Sheet
Specifications: Effective elastomer blend (black color only)
Temperature range -20°F to 170°F continuous

| <u>Typical Rubber Properties</u> | <u>Test Method</u> | <u>Typical Value</u> |
|----------------------------------|--------------------|----------------------|
| Hardness (Shore A) | ASTM D2240 | 60 ±5 |
| Tensile Strength | ASTM D412 | 700 psi min |
| Elongation | ASTM D412 | 250% min |
| Finish | Visual | Plate/Smooth |
| Color | Visual | Black |

- Thickness & Width as specified.

General Polymer Characteristics:

Thermodyn Global Sealing offers a utility grade non-fluid sealing, black rubber sheet for budget conscience applications. This material is a good option for a wide variety of industrial end uses including protective covers and shrouding applications.

Thermodyn products are manufactured to general RMA standards and meet the above data sheet guidelines. It is the responsibility of the end user to qualify the material to its intended application. Defects or damage resulting from misuse or mishandling are not covered by Thermodyn's limited liability policy. Values covered in this data sheet are nominal values that we believe to be accurate and reliable for purposes of qualification in end use applications.